

CLEAR FLAME TIP CANDLE C35

6W | 420 Lm | 2200K

Decorative, ultra dimmable LED filament light bulb with flicker-free technology and 30,000 hours lifetime. This lamp uses 6 watts of power to produce 420 lumens at a CRI of 95.

Item number: ZIK008FT/6W22E14C



LAMP


Style	C35 Candle Flame Tip
Socket	E14
Filaments	6 x 38mm
Dimmable	Yes, leading & trailing edge
LED Wattage	6w
Equivalent	40w
Lumen	420 lm
CCT LED Chip	2200K
CRI	CRI95
Glass finish	Clear
Warranty	3 years

PERFORMANCE

Lifetime	30,000 hours
Cycles on/off	100,000
Starting time	>0.2 sec
Voltage	220v-240v
Hz	50/60 Hz
In-rush protection	3000V
Power factor	>0.9
Operating temperature	-30°C to +40°C
Energy Class	A
Beam Angle	320°

DIMENSIONS

Lamp Weight	20 g
Box / inner carton qty	10 / 100



NB! This light is for indoor use only and is not suitable for use in sealed fixtures, wet environments or for integral primary optics.



EAN13 CODES

ZIK008FT/6W22E14C 5060537721880


ITF14 CODES

ZIK008FT/6W22E14C 15060537721887

Our lamps as well as the technologies behind them are subject to continuous improvements. All specification is subject to change without notice. Please refer to our website for the most up to date information.

Brand	Lamps tested	Dimmers Tested	Overall compatibility	Comments
 LUTRON [®]	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> GP Panel NGRX Interface Homeworks QS Inline Dimmer myRoom DIN-rail Power Module (Phase Adaptive) RA2 Select In-Line Dimmer 	Excellent	See Test Report
 MODE LIGHTING	GLS A60 6W CANDLE C35 4W G9 3W	<ul style="list-style-type: none"> Full Range 	Excellent	Excellent on both leading and trailing edge
 EATON <i>Powering Business Worldwide</i>	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	<ul style="list-style-type: none"> Full Range 	Very good	All lamps performed well without any issues. There were no current spikes, so, all are compatible with all of our dimmers
 VARILIGHT [®]	CANDLE C35 4W PIGMY ST26 1W GLS A60 6W G9 3W	<ul style="list-style-type: none"> V-PRO MJP120 V-PRO MJP300 V-PRO IR V-PRO MULTI-POINT V-COM 100 V-COM 180 	Excellent	Excellent compatibility rating when driven in the recommended quantities. All lamps dimmed in a smooth, progressive fashion without flickering, over an extensive brightness range. The lamps extinguish fully when in the "off state" of our remote capable dimmers
 rako	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> Full Range 	Very Good / Excellent	<p>This lamp performed very well with all dimmers with very few areas of criticism. No static flicker was observed at any output level although a slight shimmer while fading was observed with all dimmers except the WMT. While the profile was generally smooth and continuous there was a slight step around the minimum output level.</p> <p>Smoothness of Dimming Minimum brightness from off: <1% Minimum brightness from max: <1% Audible Noise: No audible noise when tested with any recommended dimmer.</p>
 Intecho	GLS A60 6W GOLFBALL G45 4W	<ul style="list-style-type: none"> Full Range 		Very good
 vivid Hospitality Solutions	GLS A60 6W GLS A60 10W GOLFBALL G45 4W GU10 6W	<ul style="list-style-type: none"> Full Range 	Very good	All the bulbs tested dim very well

Spectrum Test Report



Color Parameters:

Chromaticity Coordinate: $x=0.5131$ $y=0.4065$ $u'=0.2995$ $v'=0.5340$
 CCT=2074K (Duv=-0.0025) Dominant WL:Ld =589.1nm Purity=76.0%
 Ratio:R=34.0% G=64.3% B=1.7% Peak WL:Lp=632.4nm FWHM=110.8nm
 Render Index:Ra=92.3
 R1 =95 R2 =99 R3 =95 R4 =95 R5 =97 R6 =93 R7 =87
 R8 =78 R9 =58 R10=99 R11=98 R12=88 R13=97 R14=99 R15=89

Photo Parameters:

Flux = 478.2 lm Eff. : 80.78 lm/W Fe = 1.917 W

Electrical parameters:

V = 240.37 V I = 0.02729 A P = 5.920 W PF = 0.9026
 LEVEL:OUT WHITE:OUT

Status: Integral T = 1450 ms Ip = 21325 (33%)

Model: C35 Flame Tip Candle 6W 2200K
 Tester: OYP
 Temperature: 25.3Deg
 Manufacturer: Zico Lighting

Number: 3
 Date: 2021-09-29
 Humidity: 65.0%
 Remarks: